

**WOOD/COAL BURNING STOVE  
SUPPLEMENTAL INSPECTION FORM**

Insured's Name	Policy No.
----------------	------------

<b>Stove/Furnace Unit</b>	Type	<input type="checkbox"/> Open Hearth (No doors) <input type="checkbox"/> Pot Belly, Box or Franklin (Loose fitting doors) <input type="checkbox"/> Airtight (Tight-fitting, draft-limiting doors and seams)		
	Construction	<input type="checkbox"/> Sheet Metal <input type="checkbox"/> Cast Iron <input type="checkbox"/> Brick Lined                      Any Cracks or Broken Parts? <input type="checkbox"/> Yes <input type="checkbox"/> No		
	Fuel	<input type="checkbox"/> Wood <input type="checkbox"/> Coal <input type="checkbox"/> Other (specify):		
	Principal Use	<input type="checkbox"/> Primary Heat Source (More than 50 days/yr.) <input type="checkbox"/> Supplemental Heating (Less than 50 days/yr.) <input type="checkbox"/> Cooking		
	Installed By	<input type="checkbox"/> Owner <input type="checkbox"/> Contractor <input type="checkbox"/> Month/Year of Installation		
	Inspected By	<input type="checkbox"/> Building Inspector <input type="checkbox"/> Fire Department <input type="checkbox"/> Other (specify):		
<b>Chimney/Chimney Connector (Stove Pipe)</b>	Installation	Stove placed at least 36" from combustible well or furnishings, or 18" from non-combustible shield with 1" air space to combustible wall.	Non-combustible pad or surface below stove, extends at least 18" beyond loading door and 12" beyond side and rear.	Stove legs allow at least 4" air space below stove.
		<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
	Type	<input type="checkbox"/> Masonry <input type="checkbox"/> U.L. Listed Metal Chimney		
	Cleaned/Inspected	When last cleaned (Mo./Yr.)	Last inspected (Mo./Yr.)	Are ashes disposed of in a fireproof container? <input type="checkbox"/> Yes <input type="checkbox"/> No
Installation	Passes through non-combustible thimble collar or opening which is at least 12" larger in diameter than stove pipe:	Connector to chimney under 10' in length:	Galvanized steel pipe:	
	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	
	More than two bonds:	Horizontal portion rises at least 1/4" per linear ft. of pipe length so chimney connection point is higher than stove end:	Pipe sections overlap to contain creosote flowback:	
	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Recommendations</b>				

